Research Article

Lifecycle Cost Governance, Multi-Physics Glazing Integrity, and Edge-Level V2X Resilience in Smart Highway Infrastructure

Jessica Mercer[1,*]
[1] Northeastern University, 02115, USA
* Corresponding author: Jessica Mercer
Email: JessicaMercer@outlook.com

***Abstract*:** The deployment of cooperative vehicle-infrastructure systems along modern highway corridors frequently encounters severe fiscal overruns alongside premature degradation of roadside and vehicular hardware. While traditional governance models isolate budgetary oversight from physical asset reliability, empirical evidence suggests that financial vulnerabilities during construction often propagate into operational fragility at the edge. This study examines an integrated governance and resilience framework linking macro-level infrastructure cost control with micro-level physical and communication integrity. Specifically, the investigation synthesizes engineering-accounting review mechanisms with multi-physics durability analyses of triple-functional automotive glazing, endurance monitoring of vehicular radio-frequency power amplifiers, thermal runaway mitigation in compact lithium-ion edge sensors, and adversarial multimodal steganography for vehicle-to-everything transmissions. By critically evaluating cross-domain methodologies across these five strata, the research highlights how early capital misallocation exacerbates thermo-mechano-electromagnetic coupling failures and wireless signal attenuation under harsh highway environments. Although preliminary cross-disciplinary mapping indicates that joint engineering-financial auditing substantially reduces lifecycle maintenance liabilities, the inherent complexity of coupling fiscal incentives with real-time hardware telemetry leaves room for further empirical validation across heterogeneous regional highway networks.

Keywords: *Smart highway infrastructure; Lifecycle cost governance; Multi-physics glazing integrity; V2X communication resilience; Edge sensor safety;*

1. Introduction

Large-scale transportation infrastructure modernization has increasingly shifted from mere civil construction toward the dense integration of intelligent sensing, roadside computing, and cooperative vehicle-infrastructure communication networks. Despite substantial capital commitments, highway digitization initiatives routinely suffer from chronic budget overruns, asymmetric information between public authorities and contractors, and unexpected operational maintenance escalations once corridors enter active service. Conventional public administration literature tends to treat fiscal governance and physical systems engineering as discrete domains, assuming that contractual compliance during

procurement naturally guarantees long-term technical reliability. Yet field observations across newly commissioned smart expressways suggest a far more entangled reality, wherein deferred capital expenditures and fragmented engineering-accounting oversight directly compromise component-level material tolerances and edge communication resilience.

Recent inquiries into public infrastructure capital efficiency demonstrate that financial vulnerabilities rarely stem from isolated accounting errors; rather, they emerge from structural principal-agent conflicts embedded throughout project delivery phases[5][7]. When financial auditing remains detached from technical engineering verification, contractors face perverse incentives to substitute lower-grade materials or bypass rigorous environmental stress screening to preserve short-term margins[6][12][19]. While empirical models advocating joint engineering-financial review procedures offer a promising mechanism to curb immediate construction-phase losses, their current scope largely stops at project handover, leaving open the question of how early fiscal governance influences long-term physical degradation under coupled environmental loads.

This governance blind spot becomes particularly acute when examining the physical interfaces through which connected vehicles interact with smart highway infrastructure. Modern autonomous and connected vehicles rely heavily on laminated windshield assemblies that integrate heads-up displays, optical sensors, and radio-frequency transparent zones, all of which endure simultaneous thermal, mechanical, and electromagnetic stresses during high-speed transit[1][14]. If cost-cutting pressures during manufacturing or procurement compromise geometric curvature precision or ultraviolet-blocking coating durability, subtle optical distortions and signal attenuation can cascade into perception failures [15]. Similarly, at the wireless communication layer, on-board V2X terminals and roadside units operate under fluctuating thermal and duty-cycle conditions that accelerate radio-frequency power amplifier aging and degrade receiver sensitivity[13][20]. Compounding these hardware vulnerabilities are the challenges of maintaining reliable energy storage in compact, distributed edge sensor nodes [11] and securing multimodal data exchanges against sophisticated interception or semantic conflict[3][9].

Considering the above factors, bridging macro-level infrastructure cost governance with micro-level physical and communication resilience requires an analytical synthesis that transcends traditional disciplinary silos. Rather than proposing an idealized, seamless top-down architecture, this paper investigates the methodological intersections, trade-offs, and persistent uncertainties across five critical strata of smart highway ecosystems: lifecycle engineering-accounting governance, multi-physics automotive glazing integrity, V2X radio-frequency endurance, edge battery thermal safety, and covert multimodal communication security.

2. Multi-Layer Governance and Coupled Physical-Communication Methodology

Constructing a coherent analytical framework across financial governance and hardware reliability proved considerably less linear than initially anticipated. During the early stages of cross-referencing infrastructure auditing protocols with component-level durability testing, a fundamental methodological friction emerged: financial governance metrics operate on discrete fiscal quarters and contractual milestones, whereas physical degradation mechanisms unfold continuously across non-linear environmental stress cycles. To reconcile these divergent temporal scales, the research design was iteratively adjusted to map capital allocation decisions directly onto lifecycle reliability benchmarks, drawing inspiration from integrated multi-physics environmental stress assessments used in power

distribution systems [10] and multi-scale coupling pathways explored in low-carbon envelope optimization[17][23].

At the foundational governance layer, the methodology evaluates how engineering-accounting integration models [6] and joint engineering-financial review procedures [12] can be extended beyond initial capital expenditure auditing into operational lifecycle tracking. Rather than treating CPA practices and engineering supervision as sequential checkpoints [19], this approach examines their simultaneous application during technical specification drafting—specifically targeting high-failure-rate intelligent subsystems where initial procurement savings frequently trigger disproportionate lifecycle replacement costs[5][7]. However, translating qualitative principal-agent risk indicators into quantitative engineering tolerance thresholds remains fraught with institutional bias, as public agencies often lack the granular telemetry required to verify vendor claims during bidding.

Moving from institutional oversight to vehicular-infrastructure physical interfaces, the analytical framework scrutinizes the manufacturing and operational integrity of triple-functional integrated automotive laminated windshield glass [14]. In evaluating how geometric deviations affect embedded sensors and V2X signal transmission, attention was directed toward multi-point geometric curvature inspection frameworks utilizing unified-datum decoupling and region-aware adaptive optimization [1]. While closed-loop mold compensation techniques demonstrably enhance mass-production consistency, their reliance on idealized boundary conditions occasionally overlooks real-world weathering degradation of high UV-blocking coatings [15]. Moreover, comparing glass lamination tolerances with precision structural machining optimization in safety-critical hydraulic components [8] and digital-twin-enabled transfer molding in integrated circuit packaging [16] reveals a recurring methodological tension: hyper-local manufacturing precision increases upfront unit costs, directly challenging the strict capital expenditure ceilings imposed by public-private infrastructure budgets.

To capture the operational dynamics of wireless connectivity and edge sensing, the methodology incorporates endurance evaluation frameworks for vehicular radio-frequency (RF) subsystems alongside distributed edge node safety protocols. Specifically, automated multi-working-condition testing methods for V2X receiver sensitivity [13] and modular multi-scenario wireless simulation architectures [18] are examined in tandem with online degradation monitoring of automotive-grade RF power amplifiers [20]. Because laboratory endurance aging rarely replicates the stochastic multipath interference and thermal cycling of congested highway corridors, these RF evaluation methods were cross-examined against fleet-level mobility dynamics, including multi-agent deep reinforcement learning approaches for expanding shared e-mobility rebalancing [2, 4], which illustrate how spatial-temporal traffic fluctuations unevenly load roadside communication infrastructure. Finally, at the edge sensing and data security strata, thermal runaway early warning architectures for compact polymer lithium-ion batteries [11]—alongside lightweight neural network signal recognition and multi-sensor fusion strategies adapted from low-power embedded systems [21][22] are integrated with adversarial text-image matching steganography [3] and knowledge-conflict mitigation in language-model-driven reasoning [9] to evaluate whether covert, low-overhead data transmission can survive hardware aging without compromising semantic fidelity.

3. Critical Synthesis of Cross-Strata Vulnerabilities and Methodological Trade-Offs

Examining these diverse technical and managerial studies side by side exposes several structural vulnerabilities that remain obscured when each domain is evaluated in isolation. First, within the realm of

public infrastructure governance, empirical evaluations of engineering-accounting integration consistently demonstrate measurable reductions in construction-phase financial losses[6][19]. Yet a closer reading of these governance frameworks suggests an implicit assumption that rigorous auditing automatically aligns contractor behavior with long-term asset durability[5][12]. In practice, when budget governance mechanisms focus predominantly on capping immediate capital outlays [7], project managers may inadvertently incentivize the selection of V2X terminals or roadside sensor enclosures that pass baseline acceptance tests but exhibit accelerated degradation under prolonged field deployment.

This tension between upfront cost containment and multi-physics endurance becomes starkly apparent in the manufacturing and lifecycle performance of smart automotive glazing. Unified-datum tolerance coordination and thermo-mechano-electromagnetic coupling analyses provide a rigorous theoretical foundation for integrating optical and RF transparency within laminated windshields [14], while adaptive NSGA-II layout optimization substantially improves curvature inspection efficiency [1]. Nevertheless, these frameworks predominantly model pristine or controlled laboratory states; when high UV-blocking coatings are subjected to prolonged solar radiation, thermal shock, and mechanical vibration [15], interfacial delamination or subtle refractive shifts can degrade millimeter-wave and optical sensor accuracy in ways that static factory compensation cannot fully anticipate. Similar limitations appear in broader multi-physics reliability methodologies[10][16], where high-fidelity digital twins or coupled field simulations struggle to parameterize stochastic environmental wear without incurring prohibitive computational overhead.

Parallel methodological constraints surface in the evaluation of vehicular wireless transceivers and edge sensor hardware. Automated receiver sensitivity testing [13] and modular multi-scenario wireless simulation platforms [18] significantly improve the repeatability of V2X terminal validation compared to ad-hoc road trials. However, simulating multi-working conditions in modular chambers inevitably simplifies the non-linear thermal drift experienced by automotive-grade RF power amplifiers during extended high-duty-cycle operation [20]. When power amplifier gain compression coincides with peak traffic congestion, a dynamic captured effectively in macro-level multi-agent fleet rebalancing models[2][4]—packet loss rates can spike abruptly, rendering theoretical sensitivity margins misleading. Furthermore, as highway operators deploy dense arrays of miniaturized wireless sensors to monitor structural health and traffic flow, power management becomes critical. Early warning systems for polymer lithium-ion battery thermal runaway, originally refined within constrained wearable architectures [11], alongside lightweight neural feature extraction and multi-sensor fusion algorithms[21][22], offer compelling blueprints for low-power edge autonomy. Still, translating algorithms validated on localized acoustic or physiological signals to high-vibration, wide-temperature highway environments introduces non-trivial false-alarm risks and sensor drift biases.

At the information and security layer, the interplay between hardware degradation and semantic integrity introduces another layer of complexity. Adversarial learning combined with circle loss enhances text-image matching robustness in multimodal steganography [3], suggesting a viable pathway for embedding covert authentication signatures within routine V2X visual telemetry. Yet when wireless channels suffer from RF amplifier aging or windshield-induced signal attenuation, subtle bit errors or compression artifacts may distort the latent feature space required for accurate steganographic extraction. Likewise, while retrieval and conflict-mitigation strategies help stabilize language-model-driven decision support against contradictory inputs [9], deploying such reasoning frameworks at the network edge

remains constrained by computational budgets and the unresolved risk of cascading hallucinations when upstream physical sensors degrade simultaneously.

4. Discussion: Reconciling Fiscal Discipline with Physical-Digital Resilience

Interpreting these cross-domain findings requires moving beyond single-cause explanations of infrastructure failure. When a smart highway corridor experiences premature V2X outages or sensor blackouts, technical teams frequently attribute the failure to isolated component defects, whereas administrative auditors point to vendor non-compliance or inadequate maintenance funding. A broader synthesis suggests that both explanations capture only partial facets of a systemic coupling problem: principal-agent information asymmetries during procurement [12] systematically underprice the multi-physics degradation risks inherent in complex automotive and roadside electronics[10][14]. Because traditional accounting frameworks depreciate physical infrastructure linearly, they fail to reflect the non-linear aging curves of RF power amplifiers [20], polymeric glazing coatings [15], and lithium-ion edge batteries [11].

Alternative interpretations of this phenomenon warrant careful consideration. One could argue that the persistent gap between financial governance and physical resilience is less a failure of accounting integration[6][19] and more an inevitable consequence of rapid technological obsolescence in connected mobility. Under this view, investing heavily in ultra-durable glazing tolerance compensation [1] or exhaustive multi-scenario RF endurance testing [13][18]might yield diminishing returns if communication protocols or sensor modalities evolve faster than physical wear-out cycles. Moreover, regional disparities in climate, traffic density, and regulatory enforcement introduce substantial bias into any standardized governance model; an engineering-financial auditing protocol calibrated for temperate, high-density expressways may prove overly bureaucratic or technically misdirected when applied to extreme thermal environments [17][23]or rapidly expanding, heterogeneous e-mobility networks.

This leads us to further thinking regarding how real-time hardware telemetry might be fed back into dynamic lifecycle cost governance. If online degradation metrics from RF power amplifiers [20], battery thermal management units [11], and multi-sensor fusion nodes [22] can be aggregated without overwhelming edge bandwidth—potentially leveraging lightweight semantic compression or covert steganographic channels , infrastructure operators could transition from static capital budgeting to risk-adjusted, condition-based financial provisioning. Nevertheless, the institutional hurdles to such integration remain formidable, particularly concerning data ownership between vehicle manufacturers, telecom operators, and public highway authorities, as well as the unresolved vulnerability of edge-level AI models to adversarial manipulation and sensor noise.

5. Conclusion

Bridging macro-level public infrastructure cost governance with micro-level multi-physics hardware integrity and edge-level V2X resilience represents an essential paradigm shift for the sustainable deployment of cooperative intelligent transportation systems. By examining the structural intersections linking engineering-accounting oversight, laminated glazing durability, RF endurance monitoring, edge battery safety, and covert multimodal communication, this study underscores that fiscal discipline and physical reliability cannot be engineered in isolation; rather, sustainable highway digitization demands governance frameworks capable of internalizing non-linear material and electronic aging throughout the asset lifecycle. While synthesizing these cross-disciplinary methodologies illuminates critical blind spots in current procurement and validation practices, further empirical research is needed to establish

standardized, interoperable telemetry protocols and dynamic financial risk models that can be validated across diverse climatic and institutional highway environments.

Data Availability Statement

Data will be made available on request.

Funding

This work was supported without any funding.

Conflicts of Interest

The author(s) declare no conflicts of interest.

Ethical Approval and Consent to Participate

Not applicable.

References

[1] *Jiang, Y. (2026). Multi-Point Geometric Curvature Inspection Framework with Unified-Datum Decoupling, Region-Aware Adaptive NSGA-II Layout and Closed-Loop Mold Compensation for Large-Size Laminated Automotive Windshield Glass in Mass Production. Innovation in Science and Technology, 5(2), 69-85.*

[2] *Luo, M., Du, B., Zhang, W., Song, T., Li, K., Zhu, H., ... & Wen, H. (2023). Fleet rebalancing for expanding shared e-mobility systems: A multi-agent deep reinforcement learning approach. IEEE Transactions on Intelligent Transportation Systems, 24(4), 3868-3881.*

[3] *Hu, Y., Cao, H., Yang, Z., & Huang, Y. (2020, November). Improving text-image matching with adversarial learning and circle loss for multi-modal steganography. In International Workshop on Digital Watermarking (pp. 41-52). Cham: Springer International Publishing.*

[4] *Luo, M., Zhang, W., Song, T., Li, K., Zhu, H., Du, B., & Wen, H. (2021, January). Rebalancing expanding EV sharing systems with deep reinforcement learning. In Proceedings of the Twenty-Ninth International Conference on International Joint Conferences on Artificial Intelligence (pp. 1338-1344).*

[5] *Chen, P. (2026). Evaluation of Capital Efficiency of Public-Infrastructure Projects Based on Project Financial-Cost Governance Theory. Journal of World Economy, 5(3), 44-52.*

[6] *Peidi, C. (2026). Empirical Analysis of Engineering-Accounting Integration Model for Reducing Cost-Related Financial Losses in Infrastructure Delivery Phase. Insights in Social Science, 4(3), 45-55.*

[7] *Chen, P. (2026). Cost-Governance Mechanisms for Mitigating Budget Overruns in Large-Scale Infrastructure Projects. Frontiers in Management Science, 5(3), 43-51.*

[8] *Rusu, A. N., Dumitrascu, D. I., & Dumitrascu, A. E. (2025). Structural Integrity Enhancement and Sustainable Machining Process Optimization for Anti-Lock Braking System Hydraulic Valve Blocks. Materials, 18(23), 5287.*

[9] *Cao, H., Zhang, Z., Li, X., Wu, C., Zhang, H., & Zhang, W. (2024, December). Mitigating knowledge conflicts in language model-driven question answering. In 2024 6th International Academic Exchange Conference on Science and Technology Innovation (IAECST) (pp. 449-454). IEEE.*

[10] *Ciavarella, R., & Valenti, M. (2026). Environmental Stress-Based Reliability Assessment of Power Distribution Systems: An Integrated Multi-Physics Methodology. Electronics, 15(10), 2029.*

[11] *Lin, H. (2026). Design of Thermal Runaway Early Warning and Safety Management System for Polymer Lithium-ion Batteries in Wearable Pet Devices. Journal of Progress in Engineering and Physical Science, 5(2), 58-65.*

[12] *Peidi, C. (2026). Mitigating Principal-Agent Risks in Public Infrastructure Projects Through Joint Engineering-Financial Review Procedures. Current Research in Law & Practice, 4(2), 90-100.*

[13] *Zhao, Y. (2026). Research on Automatic Test Method of RF Receiving Sensitivity for V2X On-Board Terminals Under Multi-Working Conditions. Innovation in Science and Technology, 5(3), 9-17.*

[14] *Jiang, Y. (2026). Thermo-Mechano-Electromagnetic Multi-Physics Coupling Analysis, Unified-Datum Tolerance Coordination and Full-Lifecycle Experimental Verification of Triple-Functional Integrated Automotive Laminated Windshield Glass. Journal of Progress in Engineering and Physical Science, 5(2), 32-43.*

[15] *Yan, J. (2026). Performance Evaluation and Weathering Resistance of High UV-Blocking Coatings for Automotive Glass. Journal of Academic Research and Advances, 2(1), 53-65.*

[16] *Rosli, M. U., & Khor, C. Y. (2026). Multiphysics digital-twin-enabled transfer moulding for next-generation ic packages: a review. The International Journal of Advanced Manufacturing Technology, 1-17.*

[17] *Wang, Q., Tang, C., & Zhu, K. (2026). Mechanisms and Integrated Pathways for Tropical Low-Carbon Healthy Building Envelopes: From Multi-Scale Coupling to Intelligent Optimization. Applied Sciences, 16(1), 548.*

[18] *Yanbo, Z. (2026). Modular Architecture Design of Multi-Scenario Simulation Test Platform for Vehicular Wireless Signals. Journal of Academic Research and Advances, 2(2), 11-21.*

[19] *Chen, P. (2026). Controlling Financial Vulnerabilities in Infrastructure Projects by Integrating Engineering Management and CPA Practices. Law and Economy, 5(3), 98-105.*

[20] *Zhao, Y. (2026). Online Monitoring and Performance Degradation Evaluation Method for Automotive-Grade RF Power Amplifiers Under Endurance Aging. Journal of Progress in Engineering and Physical Science, 5(2), 66-76.*

[21] *Haipeng, L. (2026). Research on Dog Bark Recognition Algorithm Based on Mel-Frequency Cepstral Coefficients and Lightweight Neural Network. Journal of Academic Research and Advances, 2(2), 1-10.*

[22] *Lin, H. (2026). Design and Implementation of Intelligent Pet Anti-Barking Collar Control System Based on Multi-Sensor Fusion. Innovation in Science and Technology, 5(3), 1-8.*

[23] *Wang, Q., Tang, C., & Zhu, K. (2026). Mechanisms and Integrated Pathways for Tropical Low-Carbon Healthy Building Envelopes: From Multi-Scale Coupling to Intelligent Optimization. Applied Sciences, 16(1), 548.*